



## **Envoy EN2 System** **EN 2 DUAL DIVERSITY KIT**

### **Pocket Transmitters (TX)**

State of the art OLED display with navigation control for easy to use set up. Up to 24 MHz switching bandwidth in the UHF band (470 - 870MHz). Channel selection in 25 kHz steps  
Pre-programmed 32 frequencies  
User selectable frequencies with memory  
Transparent low distortion audio path with excellent dynamic range  
Adjustable microphone gain control  
Electret power for lapel microphones  
3.5mm stereo locking jack socket for audio input  
Up to 5 hours continuous use from 1 x AA (LR6) type 1.5V battery  
High quality SMA socket for transmitter aerial  
Robust lightweight aluminum housing  
Removable belt-clip

### **EN 2 DUAL DIVERSITY RECEIVER (DX2)**

State of the art OLED display with navigation control for easy to use set up  
Up to 24 MHz switching bandwidth in the UHF band (470 - 870MHz).  
Channel selection in 25 kHz steps  
Pre-programmed 32 frequencies  
Scan frequency function  
User selectable frequencies with memory  
Transparent low distortion audio path with excellent dynamic range  
Adjustable microphone level balanced output  
Adjustable headphone output for 32ohm headphones  
7 pin connector socket for audio output of Ch1 and Ch 2 plus power input.  
Up to 2 1/2 hours continuous use from 2 x AA (LR6) type 1.5V batteries or up to  
4 hours with rechargeable cells. External powering is possible with use of the appropriate cable.  
Robust lightweight aluminum housing

# En2 DDS

**KIT CONSISTS OF 2 TRANSMITTERS,  
1 DUAL DIVERSITY-DX2 (2 AUDIO CHANNELS),  
ANTENNAS FOR TRANSMITTERS AND RECEIVERS,  
2 LINE INPUT CABLES AND 1 OUTPUT CABLE.**



**Katamount**  
Enterprises Inc.

1545 The Queensway, Toronto, Ontario, M8Z 1T8  
Tel. (416) 259-3527, Fax. (416) 259-1947.  
Web site; [www.katamount.com](http://www.katamount.com)  
Email; [sales@katamount.com](mailto:sales@katamount.com)